

Noise & Vibration

Test and Measurement Solutions

for Energy & Process Industries Power Generation OII & Gas Chemical	Petrochemical
	www.oros.com

Made for Your **Demanding World**

1- Improve Efficiency

Test Cells

at OEM

> Prototype validation

> Overhaul and acceptance

2- Maximize Uptime

3- Minimize Costs

Improve acceptance testing efficiency

- > Integrated & automated test process and report generation
- > User friendly operation
- > Multi-channel real-time processing and monitoring
- > Universal and multiple sensors' types: proximity, velocity, acceleration, temperature, strain, pressure, etc

- > On-site commissioning
- > Machinery startup

Field Testing

- > Predictive maintenance
- > Installation vibration signatures

Remote Monitoring

> After installation follow-up

> Random & unrepeatable

phenomena

> Diagnostics and troubleshooting



Travel light for reliable tests

- > Versatile toolbox for all noise and vibration diagnostic applications
- > Portable and rugged analyzers for the field measurements
- Multi-channel simultaneous acquisition for run-up and coast downs
- > Real-time analysis for field efficiency
- > Full signal recording for office processing and archiving

Optimize costs and predict failure

- > Data and signals recording based on alarm level trigerring
- > Collect raw signal information for thorough office processing

OROS Solutions **Boost your Efficiency**

Based on a range of modular instruments, from 2 to 32 channels, the Teamwork technology enables to cascade or distribute the analyzers to measure up to 1000 channels. Instruments, conditioners and software licenses are exchangeable and flexible. Data are also easy to share thanks to the native technology.

SOFTWARE R&D, Acceptance, Diagnostics









- > Recorder
- > Time Domain Analysis
- > Spectral monitoring

> Turbomachinerv vibration: ORBIGate

- > Reciprocating machines diagnostics: EngineDiag
- > FFT, spectral based diagnostics > Balancing: single, dual & multiplane
- > Synchronous Order Analysis
- > Torsion & Twist

INSTRUMENTS from 2 to 32 channels, distributed up to 1000+

Flexible Connection

- > Mobile analyzer
- > Distributed configuration
- > Remote access
- > Large channel count systems

Multioperations

- > PC free recorder
- > Online & post analysis
- > Multianalysis
- > Handling any transducers

SERVICES Anywhere Close to You



- > Initial Advanced
- > Webinar

Coaching

- Sofware customization
- Assistance in your measurement



- > Troubleshooting









"From rotating analysis to structural dynamic analysis: with my OROS system, I am ready for everything when I go out in the field."

> Greg PARKER, 39 Noise and Vibration technician, Installation & Maintenance division.











- > Expertise in diagnostics
- > Tools for automation



They trust Oros







> FRF's. Resonances

- > ODS (Operating Deflection Shape)
- > Modal analysis





- > 1/3rd octave
- Sound Intensity
- > Sound Power
- > Air Holography
- > Electric motors



Made For the Field

- > Portable
- > Rugged
- > Real-time
- > Multi-channel

Accurate

- > DSP-based
- > 24 Bit 40 kHz 140 dB
- > ± 40 V input range
- > ±0.02 dB / ±0.02°



A Dedicated Team

- > Dynamic and responsive Services department
- > Worldwide hotline
- > Global Accredited Maintenance Centers (worldwide coverage)
- > Renting
- > Ready-to-go systems at any time

Maintenance and Contracts

- Premium contracts
- > Software updates
- > Hardware upgrades
- > Calibration



Measuring your Rotating Machinery

O Rotating Analysis

Fluid Film Bearings

Relative shaft vibration is captured with proximity probes. Analyzing this data requires a number of software tools such as orbit and shaft centerline as well as order analysis (nX, Bode, Polar, etc.). ORBIGate, the OROS turbomachinery vibration solution, features these analysis and many more analysis tools. These tools display the physical motion of the shaft and let you detect faults such as oil whirl & whip, preload, misalignment, rub and others.



Roller Bearings

Damaged roller bearings are common. Their vibration signatures are usually measured with an accelerometer mounted on the bearing housing. In particular, the FFT-Diagnostics module uses envelope demodulation to analyze these vibration sources to determine if the source is from the roller elements or the races.



Gear Analysis

Gear boxes have a complex vibration signature, usually occurring at high frequencies. The FFT-Diagnostics tool, such as cepstrum, kurtosis and harmonic markers are necessary to describe and understand the generated vibrations. The virtual tachometers management feature allows the analyst to determine the speed and phase information based on the gear ratio.



Reciprocating Machines Analysis

Reciprocating machines are complex installations. They generate specific vibration signatures. The objective is their performance optimization and faults detections. For example, injection delay, valves faults, segmentation wear can be identified with EngineDiag. This software module integrates the machine mechanical properties; number of cylinders, firing order and timing diagram, allowing to provide pertinent decision criteria on the field. Time signal, overall levels as well as angle-frequency representation on the machine cycle are efficient results for diagnostics.



Torsional Analysis

Torsional vibration and torque fluctuation are usual phenomena especially on large internal combustion engines. The OROS torsional software module utilizes a frequency to voltage converter for speed input providing the following information: the angular velocity profile displays RPM variations. 2 pulse train combination detects torsional resonances.



Balancing

Imbalance is probably the most common source of vibration on rotating machinery. Depending on the machine and the rotating speed range the rotor can be considered to be rigid or flexible. In the first case, the Single Dual plane balancing module will be used. In the second case a multiplane approach should be preferred and the associated Multiplane module should be used.



Electric Motors

Electric excitations can be easily characterized (PWM, slotting...) thanks to the e-markers that highlight directly the right frequencies. On top of that, the **spatiogram** is a unique tool to quickly quantify the electromagnetic excitation distribution responsible of the vibrations. Finally, sound design allows to playback and listen the motor noise separating and designing the various sources (aerodynamical, mechanical and eletromagnetic).

On-Site Measurements & Applied Trainings

Experts from OROS come on-site for applied trainings. They will help you using your OROS system. They can provide assistance in your measurement. They are also able to recommend optimization in your measurement process depending on your application and field requirements.









Turbines and Compressors

Reciprocating Machinery

> Diesel and Gas engines

Reciprocating Compressors

> Gas and Steam Turbines

> Pumps & Compressors

> Hydro Turbines

> Wind Turbines

> Fans and Blowers

- > Electric Motors
- > Power Generators











procedures.













Structural Dynamics

ODS (Operating Deflection Shape)

Operating deflection shape is an important analysis procedure used to locate machinery and piping system deflection during operation. It is based upon simplified geometry description of the machine train. After measuring the vibration response at multiple locations, the mechanical source can be identified. The ODS software module helps to determine vibration sources, a transmission point and eventually a mechanical modification to be implemented.

End Winding Bump Testing

Generators and motors end windings are strongly excited by frequencies at twice the network frequency: any mode nearby that frequency will create high vibration response. FFT analyzers and Modal, the OROS Structural Dynamics module, are well adapted for bump tests acquisition, resonance frequency determination and deflection shapes.

Blade Modal Testing

When blade dynamic structural characteristics should be determined, they are submitted to modal testing: based on impact hammer testing or shaker excitation. Based on multichannel analyzers, vibration response can be captured by accelerometers or strain gauges. Modal, the OROS Structural Dynamics module, can process the FRFs to give the modal characteristics.

Damping & Isolation

Dynamic coupling between machine trains and their skids or foundations can be a problem during the machine installation and the field acceptance test. Excitation frequencies should not match the response frequencies of the hosting structure: the mounting choice is key. To tackle this issue, OROS products such as transfer functions, ODS, and damping calculations assist the user in the

Noise Analysis

Octave & Sound Intensity

The ambient noise generated from rotating machinery can be evaluated using general tools such as the **1/3 octave analysis**. But more thorough measurements can be achieved using the sound power value. The sound intensity technique is often completed in the field thanks to its portability and adaptability.





Ordering Information

Software Modules



OROS is a global manufacturer and solution provider of noise and vibration measurement systems.

OROS masters the latest technology of data acquisition, digital signal processing as well as user interface software.

OROS instruments are used in the major sectors of industry and research, for industrial acoustics, structural dynamics and rotating machinery applications. Hardware and software are totally designed in-house.

OROS instruments are renowned as being designed for the field but powerful enough for any lab.

Rotating Analysis	
ORNVS-ORBI	ORBIGate, the dedicated Turbomachinery Vibration Solution
ORNV-SOA	Synchronous Order Analysis plug-in
ORNV-FFTDiag	Spectral Based Diagnostics software Module (Envelope, Cepstrum,
	Pk; Pk-Pk, Crest factor, shaft view)
ORNV-IVC	Integrated Instantaneous angular Velocity Converter plug-in, allows
	on-line and offline torsional analysis
ORNVS-BAL	Single Dual Plane Balancing module
ORNVS-BAL-MP	Multiplane Balancing module
ORNVS-ENGD	EngineDiag, Reciprocating Machines Diagnostics Software Module
Structural Dynamics	
ORNV-FFT	Real-time FFT plug-in
ORNVS-MOD-ODS	ODS (Operating Deflection Shape) Solution
ORNVS-MOD-MIMO	ODS (Operating Deflection Shape) and Modal Analysis Solution
Data Acquisition	
ORNV-REC	Recorder
ORNV-TDA	Real-time time domain analysis plug-in
Noise Analysis	
ORNV-OCT	Real-time filter based 1/n octave plug-in
ORNVS-SI	Sound Intensity Solution
ORNVS-SP	Sound Power Solution
ORNVS-AH	Air Holography Solution
Instruments	
Analyzers: examples of confi	gurations
Above software options may be	e added to these configurations
OR34-FREQ-4	OR34-4 Ch. FFT analyzer
OR35-FREQ-8	OR35-8 Ch. FFT analyzer
OR36-FREQ-16	OR36-16 Ch. FFT analyzer
ORMP-FREQ-16	Mobi-Pack-16 Ch. FFT analyzer
OR38-FREQ-32	OR38-32 Ch. FFT analyzer
Inputs Conditioners	
OR36/8 - PXD-B	8 Ch. Strain gauges bridge conditioner XPOD for OR36 & OR38
OR36/8 - XPOD-V	3 Display analog and digital vumeter monitoring XPod
OR36/8 - PXD-T	8 Ch. PT100 and thermocouple conditioner XPOD for OR36 & OR38
Specifications	
Channels count	2 to 1000+ channels - Distributed configuration
Inputs	
Sampling	2 kS/s to 102.4 kS/s - 24 bits delta sigma ADC

-maryzers. examples of configurat	
Above software options may be adde	ed to these configurations
DR34-FREQ-4	OR34-4 Ch. FFT analyzer
DR35-FREQ-8	OR35-8 Ch. FFT analyzer
OR36-FREQ-16	OR36-16 Ch. FFT analyzer
ORMP-FREQ-16	Mobi-Pack-16 Ch. FFT analyzer
OR38-FREQ-32	OR38-32 Ch. FFT analyzer
nputs Conditioners	
OR36/8 - PXD-B	8 Ch. Strain gauges bridge conditioner XPOD for OR36 & OR38
DR36/8 - XPOD-V	3 Display analog and digital vumeter monitoring XPod
DR36/8 - PXD-T	8 Ch. PT100 and thermocouple conditioner XPOD for OR36 & OR38
Specifications	
Channels count	2 to 1000+ channels - Distributed configuration
nputs	
Sampling	2 kS/s to 102.4 kS/s - 24 bits delta sigma ADC
Accuracy	Phase ±0.02° - amplitude ±0.02 dB - Dynamic > 160 dB
Conditioning	AC/DC/ICP/TEDS up to ±40 V
Auxiliaries	
Dutputs	DC to 40 kHz - ± 10 V range - 24 bits DACs -THD < 0.002%
Ext. synch (Trigger / Tach)	64 x over sampled (6.5MHz) - Resolution < 160 ns (0.06° @ 1 kHz) -
	up to 40 V
DC channels*	Sampling 10 Hz - 50 Hz/60 Hz rejection - reproducibility <1 mV
System	
Hard disk	128 to 512 GB SSD
nternal battery	up to 3h
_ink to PC	1 Gb/s Ethernet
Neight from	1.4 kg/3 lb to 10 kg/22 lb
Optional features	

Noise & Vibration

· pamplemousse.com | designvisuel.com - Photo credits: No Comment, nb nota bene,

specifications not binding -

Find out more on the OROS offer in the Range brochure.

Downloadable on www.oros.com



MEASURING NOISE & VIBRATION



23 chemin des pres Inovallee 4403 F-38944 Meylan Cedex Tel: +33.476.90.62.36 Fax: +33.476.90.51.37 Mail: info@oros.com Web: www.oros.com

OROS China

French Sales Office

Tel: +33.169.91.43.00 Fax: +33.169.91.29.40

Mail: info@orosfrance.fr

Web: www.oros.fr

Tel: +86.10.59892134 Fax: +86.10.59892135 Mail: info@oroschina.com Web: www.oroschina.com

OROS GmbH

Tel: +49.261.133.96.50 Fax: +49.261.133.96.49 Mail: info@oros-deutschland.com Web: www.oros-deutschland.com

OROS Americas Inc.

Tel: +1.616.202.7349 Mail: sales@oros.com Web: www.oros.com